



HELM AC (LX-HH)

TYPE:

KEY FEATURES

- Internal and external noise absorbing materials to help shut open spaces
- 2 sizes and 50 wool colors
- Standard interior in grey
- High performance dimmable LED light source (Direct) with glass diffuser
- E27/E26 lamp holder option
- Height adjustable 9' / 3m suspension cables and Black woven power cable
- IES photometric files available

OPTIONAL EXTRAS


Additional options available upon request

- POE
- Bluetooth controller (US & EU only)
- Tunable White output
- White canopy and power cord
- Contrast stitching


SIZE AND OUTPUT

SMALL (S)

MEDIUM (M)



LUMINOUS INTENSITY DISTRIBUTION



	SMALL	MEDIUM
Delivered Lumen Output	540.9lm	473.8lm
Wattage	14.5W	14.4W
Efficacy	37.4 lm/W	32.8 lm/W
UGR	<12.7	<8.8
CRI	80+	
CCT	3000, 3500, 4000 K	



ORDER CODE

EXAMPLE LED: LX - HH - M - 1Y - 35 - UNV - RD

(Luxxbox Helm AC, Medium (15"x17" / 390x422mm), in 1Y fabric, LED with 3500K CCT, Universal 0-10V 10% dimming (120-277V), Remote Driver)

EXAMPLE E26/27: LX - HH - M - 1Y - E26

(Luxxbox Helm AC, Medium (15"x17" / 390x422mm), in 1Y fabric, with an E26 lamp holder)

LX - HH									
PRODUCT CODE	SIZE		COLOR	OUTPUT		REGION / DIMMING	DRIVER TYPE		
HH	S M	11"x 12" / 275 x 306mm	Use color codes as shown	30	3000K (LED + Glass Diffuser)	UNV	0 - 10V - 10% dimming (120-277V) <i>(North America only)</i>	CD	Canopy concealed driver <i>(UNV/North America only)</i>
		35		3500K (LED + Glass Diffuser)					
		40		4000K (LED + Glass Diffuser)	G	1% dimming DSI/DALI (220 - 240V)**	RD	Remote driver <i>(UNV or G)</i>	
		E26		Edison Ø26mm <i>(North America)</i>					* E27 / E26 lampholder (10W max, LED only). Please note the light globe or driver will not be supplied with the E26/E27 option for this fixture.
E27	Edison Ø27mm								

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. June 2023. LX-Helm-AC-Spec-Sheet-v6.00



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
WWW.LUXXBOX.COM





HELM AC (LX-HH)

TYPE:


WOOL UPHOLSTERED

For any of the options below, the interior will always be in Felt Gray. See comparison between Wool Upholstered and Felt Finish at the bottom of the page for reference.



FELT FINISH

This version doesn't include any upholstery or stitching. To specify this option use color code SG (Silver Gray). In this instance, the inside of the shade will be in the same color/finish as the outside. See comparison between Wool Upholstered and Felt Finish below for reference.



NOTE: We used Wool Option 3D as an example. This would apply to all Wool options available.

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. June 2023. LX-Helm-AC-Spec-Sheet-v6.00



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
WWW.LUXXBOX.COM





HELM AC (LX-HH)



TYPE:

PHOTOMETRICS

LIGHT SOURCE SPECIFICATIONS

	SMALL	MEDIUM
Delivered Lumen Output	540.9lm	473.8lm
Wattage	14.5W	14.4W
Efficacy	37.4 lm/W	32.8 lm/W
UGR	<12.7	<8.8
CRI	>80	
CCT	3000, 3500, 4000 K	

LUMINOUS INTENSITY DISTRIBUTION




DRIVER INFORMATION

10% dimming (110 - 277V)			
Size	Watts	Output	Compliance
SMALL (Ø11"x12"H / 275 x 306mm H) MEDIUM (Ø15"x17" H/ 390 x 422mm H)	14.5W	22-42VDC	

1% dimming (DALI) (220 - 240V)			
Size	Max Output Wattage	Max Output Voltage	Compliance
SMALL (Ø11"x12"H / 275 x 306mm H) MEDIUM (Ø15"x17" H/ 390 x 422mm H)	14.5W	22-42VDC	

CANOPY INFORMATION

Please note power cord and canopy will always be supplied in black unless specified otherwise.



Luxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. June 2023. LX-Helm-AC-Spec-Sheet-v6.00



LUXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXBOX.COM
LUXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXBOX.COM
WWW.LUXBOX.COM





HELM AC (LX-HH)

TYPE:


PRODUCT ACOUSTIC PROPERTIES

Testing and post analysis procedures were carried out in accordance with the references detailed below:


AS ISO 354-2006 (R2016)	Acoustics—Measurement of sound absorption in a reverberation room
AS ISO 11654—2002	Rating of sound absorption—Materials and systems
ASTM C423-17	Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method
ASTM E795-16	Standard Practices for Mounting Test Specimens During Sound Absorption Tests
ISO 20189	Screens, furniture and single objects intended for interior use – Rating of sound absorption and sound reduction of elements based on laboratory measurements.

Below you'll find the data for both sizes of this product in Imperial and Metric units. Please note we only tested the Medium size of this product. The data for the Small size has been extrapolated from the results obtained in the testing of the Medium size pendant.

IMPERIAL SABINS	Frequency (Hz)	Sound Absorption Coefficient	SMALL (S)	MEDIUM (M)
	125	0.03	0.07	0.15
	250	0.64	1.26	2.77
	500	0.40	0.79	1.74
	1000	0.58	1.15	2.52
	2000	0.65	1.29	2.82
	4000	0.78	1.53	3.36



METRIC SABINS	Frequency (Hz)	Sound Absorption Coefficient	SMALL (S)	MEDIUM (M)
	125	0.03	0.01	0.01
	250	0.64	0.12	0.26
	500	0.40	0.07	0.16
	1000	0.58	0.11	0.23
	2000	0.65	0.12	0.26
	4000	0.78	0.14	0.31



The Sabin data shown above is in accordance with the latest International Standards for the rating of sound absorption and reduction. This is different from the classic methodology, which includes the calculation of the Noise Reduction Coefficient (NRC), the Sound Absorption Average (SAA), the Weighted Sound Absorption Coefficient (**aw**) and the Sound Absorption Class (SAC). However, to make it easier to compare against other products, we are including that information on the table on the right, which was calculated using the Largest Single Face method. Fully detailed test reports are available upon request.

NRC	0.6
SAA	0.58
aw	0.60
SAC	C

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. June 2023. LX-Helm-AC-Spec-Sheet-v6.00



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
WWW.LUXXBOX.COM






HELM AC (LX-HH)


TYPE:

PRODUCT DIMENSIONS

SMALL (S)



MEDIUM (M)



Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. June 2023. LX-Helm-AC-Spec-Sheet-v6.00



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
WWW.LUXXBOX.COM

